

72 Passenger Bus (Conv.)	YES	NO
<u>Engine/Transmission</u>		
Diesel in-line 6 cyl, w/turbo charged, minimum 200 HP. 2013 emmissions		
10 Year Mileage Engine Warranty		
Allison 2500 PTS Automatic Transmission with Temperature Gauge		
5 year / 100,000 Mile Transmission Warranty from Allison		
TransyndCR) Synthetic Automatic Transmission Fluid		
Engine Starting Aide Consisting of Heated Air Intake Grid		
Air Cleaner Restriction Gauge or Monitor		
Minimum 750 Watt, 110V Eng. Block Heater @ Body/Bumper Mounted Receptacle		
<u>Cooling</u>		
Engine Fan Clutch, Electro-Magnetic		
Extended Life Engine Coolant, Protected to -40 F		
Dash Mounted Low Coolant Warning Light		
Constant Torque Hose Clamps		
<u>Electrical</u>		
Three Group 31 Maintenance Free Batteries: 2,100 CCA		
Heavy Duty Battery Box with Sliding Battery Tray		
240 Amp Alternator with Amp Ammeter		

Minimum Two Halogen Headlights with Daytime Running Lights		
Front Amber Parking Lights and Front Amber Turn Signals, Fender Mounted		
Engine Hour Meter and Tachometer		
Warning Chime When Headlights Are On and Ignition Is Off		
<u>Axles/Tires</u>		
12,000# Front Axle with Front Parabolic Springs		
21,000# Rear Axle with 21,000# Rear Air Suspension		
11R22.5-H (14 ply) Radial Tubeless Tires		
Front Axle Oil Seals with Synthetic Oil		
Synthetic Oil, Drive Axle		
Front and Rear Frame Mounted Tow Hooks		
5.29 Rear axle Ratio		
Hub-piloted Wheels		
<u>Brakes</u>		
4 wheel disc brakes, w/anti-lock protection		
Bendix AD-IP Air Dryer		
Dual full air, Non-asbestos ext.wear lining		
Brake Dust Shields		
18.7 CFM Air Compressor or Greater		
Parking Brake Cover, EZ-Grip		
Air tank capacity @ 4260 cu.in		
<u>Fuel</u>		

100 Gallon Fuel Tank, Between Frame Rails, Mounted Behind Rear Axle, With Right Side Fill		
Heated Fuel/Water Separator		
Dash Mounted Low Fuel Warning Light in Fuel Gauge		
15 Gallon DEF Tank		
<u>Driver Convenience</u>		
Tilt/Telescoping Steering Wheel		
6-Way Adjustable Air-Ride Cloth Driver's Seat		
Air Operated Outward Opening Entrance Door		
Radio - AM/FM/PA with Eight Interior Speakers		
16 Lamp Electronic Lamp Monitor, LED capable		
Dash Mounted Digital Clock		
"Out of Normal" Range Warning Lights in All Gauges		
12V Accessory Power Socket with Cap (Cigarette Lighter Style)		
Cruise Control		
RH Modesty Panel		
Barrier Mounted Storage Pouch		
Arm Rest Compartment, Console Mounted		
Height Adjustment for Driver Shoulder Harness		
6' x 30' Interior Non-Glare Rear View Mirror		
Resettable Trip Odometer		

All Switches, Including Warning Light and Door Controls, Indirectly Illuminated		
Overhead drivers LH storage compartment		
<u>Body, Exterior</u>		
Tinted and Shaded Windshield		
Entrance Door Vandal Lock		
Emergency Door Vandal Lock with Ignition Interlock		
Wiring Access Door Vandal Lock		
Battery & Fuel Door Vandal Lock(s)		
Intermittent controlled wipers		
16 Gauge Smooth Side Panels		
Exterior Roof Painted White		
Stainless Steel Mirror Brackets		
Reflective Tape "School Bus" Front and Rear		
Reflective Tape, Side Stripe Full Length. Each Side		
Entrance Door and Driver Windows Tinted to 70% Light Transmission		
8 Lamp System with LED Lights in Stop Arm		
Four Exterior Rub Rails Including Lower Snow Rail, Painted Black		
12" Height Bumpers, After Forming, 3/16" Thick Rear and '4" Thick Front w/white reflective ID decal		
Two SMI Roof Vents / Escape Hatches		
Warning Light Visors, Front and Rear for Increased Visibility		
Heavy Duty 6" Strap Type Hinges with Zirc Grease Fittings for Emergency Door		

Body parts rustproofed before & after assembly, unit fully undercoated before mounting on chassis		
Plexiglas Cross View Heated Mirrors with Tinted Top		
Mineral Wool Insulation 1 1/2" Thick (RValue 5.75) Including Roof Bows		
Exhaust Exiting Out Rear of Bus		
Exterior Panels Fastened with Buck Rivets		
7" Back-up Lights & side underbody LED (both sides)		
Roof Mounted Strobe Light		
Low Gloss Yellow Hood with Silver Grill		
Body side windows tinted @ 30%		
<u>Body, Interior</u>		
Four Seats Shall be Seatbelt Ready		
Brown Vinyl Fire Retardant Seat Covers		
Stainless Steel Stepwell, Bolted to Body Floor Crossmembers for Ease of Replacement		
Full Length Acoustic Headliner		
Black rubber floor covering		
77" Interior Headroom		
Extra Driver's Insulation		
Interior Panels, Except Service Access Panels, Fastened with Blind Rivets		
5/8" Marine Grade Plywood Flooring, Attached with Screws to Steel Floor		
Emergency Equipment Compartment		
Glove Compartment, Dash Mounted with Door		

Two Extra Spare Circuits, 14 Gage Wire		
Dual Row Dome Lights		
3" White Abrasive Strip in Outside Edge of Step Treads		
12,000 BTU Driver Heater		
90,000 BTU Right Front Heater / Defroster, Three-Speed Fan		
50,000 BTU Front Under-Seat Heater Suspended from Seat Frame, One Two-Speed Fan		
50,000 BTU Rear Under-Seat Heater Suspended from Seat Frame, One Two-Speed Fan		
Cleanable Filters for Heaters		
Goodyear Hi-Miler Heater Hoses with Constant Torque Hose Clamps		
Sound-Off Electronic Flasher Control		
One Gallon Windshield Washer Reservoir		
Two 6" aux.fans located above windshield		
<u>Miscellaneous</u>		
Service Manuals and/or CD, Web based access		
Safety Equipment to meet Ohio State specs.		
Parts Manuals and/or CD, Web based access		
78 Passenger Bus (Conv.)	YES	NO
<u>Engine/Transmission</u>		

Diesel in-line 6 cyl, w/turbo charged, minimum 220 HP. 2013 emissions		
10 Year Mileage Engine Warranty		
Allison 2500 PTS Automatic Transmission with Temperature Gauge		
5 year / 100,000 Mile Transmission Warranty from Allison		
TransyndCR) Synthetic Automatic Transmission Fluid		
Engine Starting Aide Consisting of Heated Air Intake Grid		
Air Cleaner Restriction Gauge or Monitor		
Minimum 750 Watt, 110V Eng. Block Heater @ Body/Bumper Mounted Receptacle		
<u>Cooling</u>		
Engine Fan Clutch, Electro-Magnetic		
Extended Life Engine Coolant, Protected to -40 F		
Dash Mounted Low Coolant Warning Light		
Constant Torque Hose Clamps		
<u>Electrical</u>		
Three Group 31 Maintenance Free Batteries: 2,100 CCA		
Heavy Duty Battery Box with Sliding Battery Tray		
240 Amp Alternator with Amp Ammeter		
Minimum Two Halogen Headlights with Daytime Running Lights		
Front Amber Parking Lights and Front Amber Turn Signals, Fender Mounted		

Engine Hour Meter and Tachometer		
Warning Chime When Headlights Are On and Ignition Is Off		
<u>Axles/Tires</u>		
12,000# Front Axle with Front Parabolic Springs		
23,000# Rear Axle with 23,000# Rear Air Suspension		
11R22.5-H (14 ply) Radial Tubeless Tires		
Front Axle Oil Seals with Synthetic Oil		
Synthetic Oil, Drive Axle		
Front and Rear Frame Mounted Tow Hooks		
5.29 Rear axle Ratio		
Hub-piloted Wheels		
<u>Brakes</u>		
4 wheel disc brakes, w/anti-lock protection		
Bendix AD-IP Air Dryer		
Dual full air, Non-asbestos ext.wear lining		
Brake Dust Shields		
18.7 CFM Air Compressor or Greater		
Parking Brake Cover, EZ-Grip		
Air tank capacity @ 4260 cu.in		
<u>Fuel</u>		
100 Gallon Fuel Tank, Between Frame Rails, Mounted Behind Rear Axle, With Right Side Fill		
Heated Fuel/Water Separator		

Dash Mounted Low Fuel Warning Light in Fuel Gauge		
15 Gallon DEF Tank		
<u>Driver Convenience</u>		
Tilt/Telescoping Steering Wheel		
6-Way Adjustable Air-Ride Cloth Driver's Seat		
Air Operated Outward Opening Entrance Door		
Radio - AM/FM/PA with Eight Interior Speakers		
16 Lamp Electronic Lamp Monitor, LED capable		
Dash Mounted Digital Clock		
"Out of Normal" Range Warning Lights in All Gauges		
12V Accessory Power Socket with Cap (Cigarette Lighter Style)		
Cruise Control		
RH Modesty Panel		
Barrier Mounted Storage Pouch		
Arm Rest Compartment, Console Mounted		
Height Adjustment for Driver Shoulder Harness		
6' x 30' Interior Non-Glare Rear View Mirror		
Resettable Trip Odometer		
All Switches, Including Warning Light and Door Controls, Indirectly Illuminated		
Overhead drivers LH storage compartment		

<u>Body, Exterior</u>		
Tinted and Shaded Windshield		
Entrance Door Vandal Lock		
Emergency Door Vandal Lock with Ignition Interlock		
Wiring Access Door Vandal Lock		
Battery & Fuel Door Vandal Lock(s)		
Intermittent controlled wipers		
16 Gauge Smooth Side Panels		
Exterior Roof Painted White		
Stainless Steel Mirror Brackets		
Reflective Tape "School Bus" Front and Rear		
Reflective Tape, Side Stripe Full Length. Each Side		
Entrance Door and Driver Windows Tinted to 70% Light Transmission		
8 Lamp System with LED Lights in Stop Arm		
Four Exterior Rub Rails Including Lower Snow Rail, Painted Black		
12" Height Bumpers, After Forming, 3/16" Thick Rear and '4" Thick Front w/white reflective ID decal		
Two SMI Roof Vents / Escape Hatches		
Warning Light Visors, Front and Rear for Increased Visibility		
Heavy Duty 6" Strap Type Hinges with Zinc Grease Fittings for Emergency Door		
Body parts rustproofed before & after assembly, unit fully undercoated before mounting on chassis		
Plexiglas Cross View Heated Mirrors with Tinted Top		

Mineral Wool Insulation 1 %' Thick (RValue 5.75) Including Roof Bows		
Exhaust Exiting out side of Bus		
Exterior Panels Fastened with Buck Rivets		
7" Back-up Lights & side underbody LED (both sides)		
Roof Mounted Strobe Light		
Low Gloss Yellow Hood with Silver Grill		
Body side windows tinted @ 30%		
<u>Body, Interior</u>		
Four Seats Shall be Seatbelt Ready		
Brown Vinyl Fire Retardant Seat Covers		
Stainless Steel Stepwell, Bolted to Body Floor Crossmembers for Ease of Replacement		
Full Length Acoustic Headliner		
Black rubber floor covering		
77' Interior Headroom		
Extra Driver's Insulation		
Interior Panels, Except Service Access Panels, Fastened with Blind Rivets		
5/8" Marine Grade Plywood Flooring, Attached with Screws to Steel Floor		
Emergency Equipment Compartment		
Glove Compartment, Dash Mounted with Door		
Two Extra Spare Circuits, 14 Gage Wire		
Dual Row Dome Lights		
3" White Abrasive Strip in Outside Edge of Step Treads		
12,000 BTU Driver Heater		

90,000 BTU Right Front Heater / Defroster, Three-Speed Fan		
50,000 BTU Front Under-Seat Heater Suspended from Seat Frame, One Two-Speed Fan		
50,000 BTU Rear Under-Seat Heater Suspended from Seat Frame, One Two-Speed Fan		
Cleanable Filters for Heaters		
Goodyear Hi-Miler Heater Hoses with Constant Torque Hose Clamps		
Sound-Off Electronic Flasher Control		
One Gallon Windshield Washer Reservoir		
Two 6" aux.fans located above windshield		
<u>Miscellaneous</u>		
Service Manuals and/or CD, Web based access		
Safety Equipment to meet Ohio State specs.		
Parts Manuals and/or CD, Web based access		
84 Passenger Bus (Transit)	YES	NO
<u>Engine/Transmission</u>		
Diesel in-line 6 cyl, w/turbo charged, minimum 220 HP. 2013 emmissions		
10 Year Mileage Engine Warranty		
Allison 2500 PTS Automatic Transmission with Temperature Gauge		

5 year / 100,000 Mile Transmission Warranty from Allison		
TransyndCR) Synthetic Automatic Transmission Fluid		
Engine Starting Aide Consisting of Heated Air Intake Grid		
Air Cleaner Restriction Gauge or Monitor		
Minimum 750 Watt, 110V Eng. Block Heater @ Body/Bumper Mounted Receptacle		
<u>Cooling</u>		
Engine Fan Clutch, Electro-Magnetic		
Extended Life Engine Coolant, Protected to -40 F		
Dash Mounted Low Coolant Warning Light		
Constant Torque Hose Clamps		
<u>Electrical</u>		
Two Group 8D Batteries, 12 volt		
Heavy Duty Battery Box with Sliding Battery Tray		
240 Amp Alternator with Amp Ammeter		
Minimum Two Halogen Headlights with Daytime Running Lights		
Front Amber Parking Lights and Front Amber Turn Signals		
Engine Hour Meter and Tachometer		
Warning Chime When Headlights Are On and Ignition Is Off		
<u>Axles/Tires</u>		

13,200# Front Axle with Front Parabolic Springs		
23,000# Rear Axle with 23,000# Rear Air Suspension		
11R22.5-H (16 ply) Radial Tubeless Tires		
Front Axle Oil Seals with Synthetic Oil		
Synthetic Oil, Drive Axle		
Front and Rear Frame Mounted Tow Hooks		
5.29 Rear axle Ratio		
Hub-piloted Wheels		
<u>Brakes</u>		
4 wheel disc brakes, w/anti-lock protection		
Bendix AD-IP Air Dryer		
Dual full air, Non-asbestos ext.wear lining		
Brake Dust Shields		
18.7 CFM Air Compressor or Greater		
Parking Brake Cover, EZ-Grip		
Air tank capacity @ 4400 cu.in		
<u>Fuel</u>		
100 Gallon Fuel Tank, Between Frame Rails, Mounted Behind Rear Axle, With Right Side Fill		
Heated Fuel/Water Separator		
Dash Mounted Low Fuel Warning Light in Fuel Gauge		
15 Gallon DEF Tank		
<u>Driver Convenience</u>		
Tilt/Telescoping Steering Wheel		

6-Way Adjustable Air-Ride Cloth Driver's Seat		
Air Operated Outward Opening Entrance Door		
Radio - AM/FM/PA with Eight Interior Speakers		
16 Lamp Electronic Lamp Monitor, LED capable		
Dash Mounted Digital Clock		
"Out of Normal" Range Warning Lights in All Gauges		
12V Accessory Power Socket with Cap (Cigarette Lighter Style)		
Cruise Control		
Barrier Mounted Storage Pouch		
LH Arm Rest @ rear portion of switch panel		
Height Adjustment for Driver Shoulder Harness		
6' x 30' Interior Non-Glare Rear View Mirror		
Resettable Trip Odometer		
All Switches, Including Warning Light and Door Controls, Indirectly Illuminated		
Overhead drivers LH storage compartment		
<u>Body, Exterior</u>		
Tinted and Shaded Windshield		
Entrance Door Vandal Lock		
Emergency Door Vandal Lock with Ignition Interlock		
Wiring Access Door Vandal Lock		
Battery & Fuel Door Vandal Lock(s)		

Intermittent controlled wipers		
16 Gauge Smooth Side Panels		
Exterior Roof Painted White		
Stainless Steel Mirror Brackets		
Remote control heated side body mirrors		
Reflective Tape "School Bus" Front and Rear		
Reflective Tape, Side Stripe Full Length. Each Side		
Entrance Door and Driver Windows Tinted to 70% Light Transmission		
8 Lamp System with LED Lights in Stop Arm		
Four Exterior Rub Rails Including Lower Snow Rail, Painted Black		
12" Height Bumpers, After Forming, 3/16" Thick Rear and '4" Thick Front w/white reflective ID decal		
Two SMI Roof Vents / Escape Hatches		
Warning Light Visors, Front and Rear for Increased Visibility		
Heavy Duty 6" Strap Type Hinges with Zinc Grease Fittings for Emergency Door		
Body parts rustproofed before & after assembly, unit fully undercoated before mounting on chassis		
Plexiglas Cross View Heated Mirrors with Tinted Top		
Mineral Wool Insulation 1 1/2" Thick (RValue 5.75) Including Roof Bows		
Exhaust Exiting Out Rear of Bus		
Exterior Panels Fastened with Buck Rivets		
7" Back-up Lights & side underbody LED (both sides)		

Roof Mounted Strobe Light		
Body side windows tinted @ 30%		
RH mid-mount storage compartment 22" x25"x97"		
<u>Body, Interior</u>		
Four Seats Shall be Seatbelt Ready		
Brown Vinyl Fire Retardant Seat Covers		
Stainless Steel Stepwell, Bolted to Body Floor Crossmembers for Ease of Replacement		
Full Length Acoustic Headliner		
Black rubber floor covering		
77' Interior Headroom		
Extra Driver's Insulation		
Interior Panels, Except Service Access Panels, Fastened with Blind Rivets		
5/8" Marine Grade Plywood Flooring, Attached with Screws to Steel Floor		
Emergency Equipment Compartment		
Two Extra Spare Circuits, 14 Gage Wire		
Dual Row Dome Lights		
3" White Abrasive Strip in Outside Edge of Step Treads		
12,000 BTU Driver Heater		
90,000 BTU Right Front Heater / Defroster, Three-Speed Fan		
50,000 BTU Front Under-Seat Heater Suspended from Seat Frame, One Two-Speed Fan		
50,000 BTU Rear Under-Seat Heater Suspended from Seat Frame, One Two-Speed Fan		

Cleanable Filters for Heaters		
Goodyear Hi-Miler Heater Hoses with Constant Torque Hose Clamps		
Sound-Off Electronic Flasher Control		
One Gallon Windshield Washer Reservoir		
Two 6" aux.fans located above windshield		
<u>Miscellaneous</u>		
Service Manuals and/or CD, Web based access		
Safety Equipment to meet Ohio State specs.		
Parts Manuals and/or CD, Web based access		